

ALARM BELLS , EAB SERIES EXPLOSION PROOF



BELGIUM

A QUALITY PRODUCT

APPLICATION

The EAB alarm bells are used as alarm or signal devices for a various purposes. They are designed for zone 1, 2 and zone 22 hazardous areas.

TECHNICAL DATA

Type of Protection	: Ex d IIB T6
Conforming to	: Standards IEC 60079-0 to 1 or UL 60079-1
Marking for test	: Ex II2G
Degree of Protection	: IP 65 acc.To IEC 60529
Ambient Temp. (Ta)	: -20° C to+ 55° C
Rated Voltage	: 12 - 24V.DC., 110 - 220V.AC. 50Hz.
Protection class for UL	: Class I,II Division 1 or 2 Group.C,D,E,F and G
Entries thread	: 3/4" NPT through-feed(optional 4-ways)



SPECIFICATION

Body	: Marine Grade Copper-free aluminium alloy with polyester powder coated RAL7032 (GREY)
Gong	: Sheet with polyester powder coated 3020 (Red)

CATALOGUE NUMBER

Supply Voltage	Amp.	VA.	Bell Dia.	Sound Level at 10 ft.(dB.)	Cat. No.
24V.DC.	0.03	0.72	6 inches	85	EAB 24C
110 V.AC.	0.047	5.2	6 inches	85	EAB 110C
220V.AC.	0.024	5.2	6 inches	85	EAB 220C

DIMENSION IN M

