



**BELGIUM**

A QUALITY PRODUCT

**EMERGENCY CONTROL STATIONS (Break-Glass)**

**EBG SERIES  
EXPLOSION PROOF**

**TECHNICAL DATA**

Type of Protection : Ex d IIB T6  
 Conforming to : Standards IEC 60079-1 or UL 60079-1  
 Marking for test : Ex II2G  
 Degree of Protection : IP66 acc.To IEC 60529  
 Ambient Temp. (Ta) : -20°C to+ 55° C  
 Protection class for UL. : Class I, Division1 or 2 Group.C,D  
 : Class II, Division 1 or 2 Groups.E,F,G  
 Protection class for IEC : Zone1and Zone 2  
 Conduit hub : : 3/4"x 2 NPT. With Stopping Plug 3/4" x 1  
 Button : 3A 220VAC. (10A.Rated thermal current)



**SPECIFICATION**

Body and cover : Copper-free aluminium  
 Bolts and operating shaft : Stainless steel

**CATALOGUE NUMBER**

Momenritary		
Contact	Entries threaded(NPT)	Cat.,No.
1NO	3/4"	EBG-A-N2
1NC	3/4"	EBG-B-N2
1NO-1NC	3/4"	EBG-A-N2

**DIMENSION IN MM.**

