

BELGIUM



A QUALITY PRODUCT

EMERGENCY LIGHT ,EEMG Series EXPLOSION PROOF



TECHNICAL DATA

Type of Protection	: Ex de IIB T6
Conforming to	: Standards IEC 60079-0 to 1 or UL 60079-1
Marking for test	: Ex II2G
Degree of Protection	: IP 66 / 67 acc.To IEC 60529
Ambient Temp. (Ta)	: -20° C to + 40° C or 55° C
Rated Voltage	: 220 - 240 V.AC. 50/60Hz. Output 12V.DC.
Lamp	: 2 x 35 W. , 2 x 55 W.
Battery	: 6V. 4Ah.
Recharge time	: 24 hours from fully discharge
Emergency duration	: 2-hours
Protection class for UL.	: Class I, Division 1 or 2 Group.C,D : Class II, Division 1 or 2 Groups.E,F,G
Protection class for IEC	: Zone 1 and Zone 2

SPECIFICATION

Body material	: Marine Grade Copper-free aluminium alloy with polyester powder coated RAL7032 (GREY)
Sealing gasket	: Silicone -40° C to +175° C
Lid screws	: Stainless steel

CATALOGUE NUMBER AND DIMENSION

Lamp watts	Cat.,No.	Temp Class	
		T40°C	T55°C
2 x 35 w	EEMG235	T5	T4
2 x 50 w	EEMG250	T5	T4

