



BELGIUM

A QUALITY PRODUCT

EMERGENCY PUSH BUTTOMS EEM SERIES

EXPLOSION PROOF

TECHNICAL DATA

Type of Protection : Ex d IIB T6
 Conforming to : Standards IEC 60079-1 or UL 60079-0/1
 Marking for test : Ex II2G
 Degree of Protection : IP65/66 acc.To IEC 60529
 Ambient Temp. (Ta) : -20° C to+ 55° C
 Protection class for UL. : Class I, Division1 or 2 Group.C,D
 : Class II, Division 1 or 2 Groups.E,F,G
 Protection class for IEC : Zone1and Zone 2



SPECIFICATION

Body, cover and handle : Copper-free aluminium
 Bolts and operating shaft : Stainless steel

OPTIONS

Silicone rubber on cover pushbutton
 Type S for IP66
 1/2 inch NPT size conduit hub.

CATALOGUE NUMBER

Number of contact	Symbol	Nameplate Marking	Cat.,No.	
			Dead-end (1 hub)	Through-feed (2 hub)
Momentary 1NC		EMERGENCY STOP	EEM 01	EEM 01H
1NO-1NC		EMERGENCY STOP	EEM 11	EEM 11H
Push - Lock , Turn - Reset 1NC		EMERGENCY STOP	EEM 01L	EEM 01LH
1NO-1NC		EMERGENCY STOP	EEM 11L	EEM 11LH

DIMENSION IN MM.

